

MUFFLER & TAILPIPE SEALANT PART NO. 49411

PHYSICAL PROPERTIES

Physical Form.....	Paste
Specific Gravity.....	1.9
Color	Red
Odor.....	Slight
Density lbs/Gal.	15.85
Solubility.....	Dilutable in wet stage
VOC %	0 grams/liter
Percent Volatile	20
Viscosity	750,000 cPs

DESCRIPTION

Dynatex® Muffler & Tailpipe Sealant is a single component, non-slumping sealant that sets to form a hard surface. **Dynatex® Muffler & Tailpipe Sealant** serves to form a “gasket or seal against air infiltration”. Repairs holes and leaks in muffler, tailpipes and around joints. Makes new installations more secure.

FEATURES

- Easy to use
- Repairs leaks
- Waterproof
- Non-combustible
- Single component system, no mixing necessary
- Non-shrinking
- Easily applied sealant with water clean up capabilities

TYPICAL APPLICATIONS

- Mufflers, tailpipes, exhaust pipes and catalytic converters
- Seals connections in exhaust systems



TEMPERATURE RANGE

Dynatex® Muffler & Tailpipe Sealant freezes in the tube at temperatures below 32°F (0°C). The product can be warmed and applied at any temperature, but will not cure below 40°F (4°C). Freeze thaw cycles do not alter the cured product.

TYPICAL CURING PERFORMANCE

Dynatex® Muffler & Tailpipe Sealant cures by the evaporation of water and further cures with heat. Full cure will be affected after 24 hours of drying and driving at the maximum operating temperature.

DIRECTIONS FOR USE

1. Surfaces to be repaired should be free of dirt, grease, oil and rust.
2. Wet the surface to be repaired with water.
3. Apply the sealer directly over the hole.
4. Allow to dry for 30 minutes, then start engine and allow to run for 10 more minutes.
5. For new installations, apply sealer around inside of larger pipe. Complete and seal the connection.

STORAGE AND SHELF LIFE

When stored in the original unopened containers at or below 90°F (32°C), **Dynatex® Muffler & Tailpipe Sealant** has a shelf life of 12 months from date of shipment.

In Countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

TRANSPORTATION INFORMATION

DOT Road Shipment Information

DOT (USA) Caulking Compound
DOT Hazard Classification.....None
UN/NA NumberNot applicable
Label RequiredNone

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it the user's responsibility to determine suitable of use. Since the supplier cannot know all the uses, or the conditions of use to which there products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no use, nor any other express or implied warranty. The users exclusive remedy and the suppliers sole liability is limited to refund of the purchase price or replacement of any product when to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.



Dynatex
350 Ring Road
Elizabethtown
Kentucky 42701 USA
(800) 999-2937
TEL (270) 769-5557
FAX (270) 769-6418
Outside U.S.
TEL +1(270) 769-5557
FAX +1(270) 769-6418

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662) 634-3060
FAX (662) 634-3066

Email: sales@dynatexinc.com
Website: www.dynatexinc.com